



Guanghai PVC flexible tube details:

General PVC tubes are mainly used to transport liquids and insulation protection, mainly used in electronic, medical, communications, agriculture, fishery, and lighting etc. It has good acid, corrosion-resistant and fire retardan

Product Type	PVC tube
Material	PVC
Flame retardant	VW-1
Operation Temperature	-35℃-75℃
Withstand Voltage	600V
Specification	Customized
BPA Free	Yes
Working pressure(at room temper ature)	2~2.5Pa
Feature	Light, Durable, Flexible, Soft etc
Usage	Transport liquid and gas, electronic, lighting
Place of Origin	Guangdong, China (Mainland)

General size

Inner Diameters(mm)	Thickness(mm)	Outer Diameters (mm)	Material
$\Phi 1.0\pm0.1$	0.30 ± 0.05	$\Phi 1.6\pm0.1$	PVC
$\Phi 1.5\pm0.1$	0.35 ± 0.05	$\Phi 2.2\pm0.1$	PVC
$\Phi 2.0\pm0.1$	0.50 ± 0.05	$\Phi 3.0\pm0.1$	PVC
$\Phi 2.5\pm0.1$	0.50 ± 0.05	$\Phi 3.5\pm0.1$	PVC
$\Phi 3.0\pm0.1$	0.50 ± 0.05	$\Phi 4.0\pm0.1$	PVC
$\Phi 3.5\pm0.1$	0.50 ± 0.05	$\Phi 4.5\pm0.1$	PVC
$\Phi 4.0\pm0.1$	0.50 ± 0.05	$\Phi 5.0\pm0.1$	PVC
$\Phi 4.5\pm0.1$	0.50 ± 0.05	$\Phi 5.5\pm0.1$	PVC
$\Phi 5.0\pm0.1$	0.50 ± 0.05	$\Phi 6.0\pm0.15$	PVC
$\Phi 5.5\pm0.1$	0.50 ± 0.05	$\Phi 6.5\pm0.15$	PVC
$\Phi 6.0\pm0.1$	0.50 ± 0.05	$\Phi 7.0\pm0.15$	PVC
$\Phi 6.5\pm0.1$	0.50 ± 0.05	$\Phi 7.5\pm0.2$	PVC
$\Phi 7.0\pm0.1$	0.50 ± 0.05	$\Phi 8.0\pm0.2$	PVC
$\Phi 7.5\pm0.1$	0.50 ± 0.05	$\Phi 8.5\pm0.2$	PVC
$\Phi 8.0\pm0.1$	0.50 ± 0.05	$\Phi 9.0\pm0.2$	PVC
$\Phi 8.5\pm0.1$	0.50 ± 0.05	$\Phi 9.5\pm0.2$	PVC
$\Phi 9.0\pm0.1$	0.50 ± 0.05	$\Phi 10.0\pm0.2$	PVC
$\Phi 9.5\pm0.1$	0.50 ± 0.05	$\Phi 10.5\pm0.2$	PVC
$\Phi 10.0\pm0.1$	0.50 ± 0.05	$\Phi 11.0\pm0.2$	PVC

Guanghai Electronic Insulation Materials Co.,Ltd professional in kind of insulation tubes and coated webbing , any interested ,please contact us info@gh-material.com

Address :(Plant) 3/F, No. 154, Huasheng East St.,
Chenjiang Street, Zhongkai High-Tech Zone,
Huizhou, Guangdong, China (Mainland)
Tel/Fax:86-752-3175209
Website: <http://www.gh-material.com>



